

BRASIL ABS

COLLECTION CLASSIC

TECHNICAL CHARACTERISTICS 0-500gr/6' Max 2Kg

Voltage: 230V / 220V / 110V Frequency: 50Hz / 60Hz

Phases: 1(monophase)

RPM: 1.300 / 1.600

Current: 1.4A / 3A

Capacitor: 9nf / 40nf

Power: 0,12 Hp / 275W

Protection rating: IP21

Motor supplied with thermal protector

Maximum operating time: 30 min.

Tempered steel grinding wheel (62HRc) Ø 60mm

Lifespan of grinding wheels: 500kg

Hopper capacity: 1kg

Doser capacity: 300g

Doser regulation: 5/12g

Doser lever: right/left

Stop/start standard version: manual

Optional: automatic start


Dimensions width x length x height: 210x380x470mm

Weight: 8 kg

Air noise: 77dB

Diseñado bajo directiva 89/392 CE













GREY

DARK GREY

BLACK

PURPLE













MAIN ATTRIBUTES

Hopper (1kg) made of unbreakable and non-deformable material (co.polyester), with fast lock system and self-levelling when off the coffee grinder, with the possibility of cleaning in a dishwasher at 90 °C. Micrometric regulation of the coffee grind using a regulatory pawl. New expulsion system for the ground coffee (always leaving the grinding cavity clean when the coffee grinder stops). Bodywork manufactured in anti-scratch material, in a single piece (less vibrations, more robustness). With ventilation system (internal air inlet and outlet). Large tray integrated into the body, ready to take knocks (portafilter). Single-bodied, hermetically sealed doser without aroma loss, vibrationless and made of unbreakable material. Ergonomic handle. Universal coffee tamper (rotatable). Doser fitted with gasket-saver (portafilter positioner). Hardened steel grinding blades (62/65HRc) 60mm in diameter.

Optional: Left- or right-handed doser lever. Coffee counter. Optional personalisation system with chrome plates on the doser and on the rear of the bodywork. Automatic stop/start every two cups (depending on filling doser).



Тел./факс: +74955404600